





**PIGNONI SEMPLICI PER CATENE A RULLI IN ACCIAIO INOX - DIN 8187 - ISO 606**  
**SIMPLEX SPROCKETS IN STAINLESS STEEL FOR ROLLER CHAINS - DIN 8187 - ISO 606**

**3/8" x 7/32"**

**9,525 x 5,72 mm**  
**Rullo 6,35 mm**  
**06B - 1**





B1	C	r3
5,3	1	10

Materiale INOX AISI 304 L

Z	de	dp	dm	D1	A	Kg.	Z	de	dp	dm	D1	A	Kg.
13	43,5	39,80	28	8	25	0,13	20	64,6	60,89	46	10	28	0,39
14	46,5	42,80	31	8	25	0,16	21	67,6	63,91	48	12	28	0,42
15	49,5	45,81	34	8	25	0,18	23	73,7	69,95	52	12	28	0,50
16	52,5	48,82	37	10	28	0,24	25	79,7	76,00	57	12	28	0,60
17	55,5	51,83	40	10	28	0,28	30	94,8	91,12	60	12	30	0,72
18	58,6	54,85	43	10	28	0,33							
19	61,6	57,87	45	10	28	0,36							

**1/2" x 5/16"**

**12,7 x 7,75 mm**  
**Rullo 8,51 mm**  
**08B - 1**





B1	C	r3
7,2	1,3	13

Materiale INOX AISI 304 L

Z	de	dp	dm	D1	A	Kg.	Z	de	dp	dm	D1	A	Kg.
12	53,9	49,07	33	10	28	0,21	19	82,0	77,16	60	12	28	0,67
13	57,9	53,06	37	10	28	0,26	20	86,0	81,19	64	12	28	0,76
14	61,9	57,07	41	10	28	0,32	21	90,1	85,22	68	14	28	0,85
15	65,9	61,09	45	10	28	0,38	23	98,1	93,27	70	14	28	0,94
16	69,9	65,10	50	12	28	0,46	25	106,2	101,33	70	14	28	1,01
17	74,0	69,11	52	12	28	0,51	30	126,3	121,50	80	16	30	1,46
18	78,0	73,14	56	12	28	0,59							

**5/8" x 3/8"**

**15,875 x 9,65 mm**  
**Rullo 10,16 mm**  
**10B - 1**



B1	C	r3
9,1	1,6	16

Materiale INOX AISI 304 L



Z	de	dp	dm	D1	A	Kg.	Z	de	dp	dm	D1	A	Kg.
13	73,2	66,32	47	12	30	0,46	20	108,4	101,49	75	14	30	1,21
14	78,2	71,34	52	12	30	0,56	21	113,4	106,52	75	16	30	1,35
15	83,2	76,36	57	12	30	0,67	23	123,5	116,58	80	16	30	1,47
16	88,3	81,37	60	12	30	0,76	25	133,6	126,66	80	16	30	1,60
17	93,3	86,39	60	12	30	0,88	30	158,8	151,87	90	20	35	2,41
18	98,3	91,42	70	14	30	1,01							
19	103,3	96,45	70	14	30	1,15							



**PIGNONI SEMPLICI PER CATENE A RULLI IN ACCIAIO INOX - DIN 8187 - ISO 606**  
**SIMPLEX SPROCKETS IN STAINLESS STEEL FOR ROLLER CHAINS - DIN 8187 - ISO 606**

**3/4" x 7/16"**

**19,05 x 11,68 mm**  
**Rullo 12,07 mm**  
**12B - 1 - 2 - 3**



B1	C	r3
11,1	2	19



Materiale INOX AISI 304 L

Z	de	dp	dm	D1	A	Kg.
13	87,8	79,59	58	16	35	0,80
14	93,8	85,61	64	16	35	0,97
15	99,8	91,63	70	16	35	1,16
16	105,8	97,65	75	16	35	1,34
17	111,9	103,67	80	16	35	1,53
18	117,9	109,71	80	16	35	1,62
19	123,9	115,75	80	16	35	1,70

Z	de	dp	dm	D1	A	Kg.
20	130,0	121,78	80	16	35	1,80
21	136,0	127,82	90	20	40	2,35
23	148,1	139,90	90	20	40	2,56
25	160,2	152,00	90	20	40	2,80

**1" x 17,02 mm**

**25,4 x 17,02 mm**  
**Rullo 15,88 mm**  
**16B - 1**



B1	C	r3
16,2	2,5	26

Materiale INOX AISI 304 L

Z	de	dp	dm	D1	A	Kg.
13	117,7	106,12	78	16	40	1,77
14	125,7	114,15	84	16	40	2,08
15	133,7	122,17	92	16	40	2,46
16	141,8	130,20	100	20	45	3,14
17	149,8	138,22	100	20	45	3,34
18	157,8	146,28	100	20	45	3,56
19	165,9	154,33	100	20	45	3,78

Z	de	dp	dm	D1	A	Kg.
20	173,9	162,38	100	20	45	4,03
21	182,0	170,43	110	20	50	5,14